

## AXIS Q60 Series

AXIS Q6074



AXIS Q6074-E



	AXIS Q6074	AXIS Q6074-E
<b>Max. video resolution</b>	1280x720 (1 MP)	1280x720 (1 MP)
<b>Sensor size/Lens/ Horizontal field of view</b>	1/2.8" 4.25–127.5 mm, F1.6–4.2, 63.8°–2.6° (720p), 49.7°–1.73° (D1)	1/2.8", 4.25–127.5 mm, F1.6–4.2, 63.8°–2.6° (720p), 49.7°–1.73° (D1)
<b>Day and night</b>	✓	✓
<b>Min. illumination (lux) Color/B&amp;W</b>	0.1/ 0.002	0.1/ 0.002
<b>Max. frames per second</b>	50/60	50/60
<b>Optical zoom</b>	40	40
<b>Audio support/ Built-in mic</b>	✓ / - / -	- / -
<b>Product specific analytics (for standard analytics, see page 43)</b>	AXIS Guard Suite Audio detection Autotracking Active Gatekeeper Standard analytics	AXIS Guard Suite Audio detection Autotracking Active Gatekeeper Standard analytics
<b>Power</b>	PoE Class 4, AC, DC Midspan included	High PoE SFP midspan included
<b>In-/output ports</b>	4	-
<b>Operating temperature</b>	0 °C to 50 °C (32 °F to 122 °F)	-50 °C to 50 °C (-58 °F to 122 °F)
<b>Outdoor ready approvals</b>	-	IP66/IP67/NEMA 4X
<b>WDR</b>	WDR	WDR
<b>Lightfinder</b>	Lightfinder 2.0	Lightfinder 2.0
<b>Zipstream/H.264/H.265</b>	✓ / ✓ / -	✓ / ✓ / -
<b>OptimizedIR/Built-in IR</b>	- / -	- / -
<b>Special features</b>	Electronic image stabilization Automatic defog Focus recall Object counter Object removed Shock detection Highlight compensation	Electronic image stabilization Automatic defog Focus recall Object counter Object removed IK10 Shock detection Highlight compensation