

Easy Pull Fan-out/ Patch Cable/Trunk Cable



WONDERFUL

- LC接頭採用易拆式高密度使用時可單獨快速拔取安裝及跳接
- 採用圓形雙芯外徑3.0mm適用於機房內高密度安裝整理跳接
- 12C MPOMTP FAN-OUT扇形跳線採用6條雙心3.0mm圓形線
- MPO/MTP主幹纜可加裝拉線網環’ 保護接頭在佈纜時不易受損
- LC採雙芯一體快拆設計’ 可快速開啟變換平行接點為交叉線位
- 全系列採用耐彎型光纖絲
- 外被採用高阻燃OFNP或LSZH

◆ 符合標準

- ANSI/TIA942
- TIA/EIA 568 C3
- ITU-T G.657.A1, A2
- ITU-T G.651. OM3, OM4
- IEC 60793 IEC 60794
- ANSI/TIA/EIA 492AAA/492AAB
- RoHS compliant (2011/65/EU)

◆ 產品描述

- UL OFNR OFNP
- IEC-60332-1/IEC- 60332-3
- IEC- 60754 / IEC -61034

◆ 應用範圍

- 10/100/1000 Base FX/SX
- 10G Base E/S/L/LX4/LRM
- 40G Base LR4/SR4
- 100G Base LR4/ER4/SR10



Trunk Cable

OM3 WMTPM312CXXM-JE =01M~∞M
單模 WMTPM912CXXM-JE =01M~∞M

Easy Pull Patch Cable

OM3 WFP3MLLXXDDH-JE =01M~∞M
單模 WFC9LAUXXDDH-JE =01M~∞M



FAN-OUT Cable

OM3 WMTPM312LMXXM-JE=1M~∞M
單模 WMTPM912LMXXM-JE=1M~∞M

產品描述

MPO/MTP Module Level I IL		< 0.35 dB / RL>55dB (Typical)
LC/SC S/M	IL	<0.15dB/ RL > 55dB (Typical)
LC/SC M/M	IL	<0.25dB (Typical)

★ (xx)顏色:GY、WH、RED、BU、GR、YL、OR

本產品型錄規格如有爭議以本公司解釋為主並保留變更修改之權利